



Technical features

Item Id.	EP-032570
drive turning direction	R.H./L.H.
drive speed max.	permanent operation 6.752 rpm
drive speed max.	interval operation 8.102 rpm
number of spindles	1
spindle position	horizontal to vertical adjustable by scale (0° - 100°)
tool receptacle	1x ø75 x ø30j5 x 1,5-5 mm clamping area 1x shank receptacle ø10H7
gear ratio	1 : 1,48 – toothed belt and gear drive
turning direction of tool receptacle	2x opposite to drive turning direction
spindle speed max.	permanent operation 10.000 rpm
spindle speed max.	interval operation 12.000 rpm
drive capacity	3,0 kW
weight without drive adapter	approx. 3,20 kg

Optional accessories:

Indexing 45°/67,5°/90°
Hex-wrench SW3
Hex-wrench SW4
Hex-wrench SW6
Lubrication press

Item Id. 032549
Item Id. 138030
Item Id. 138040
Item Id. 138060
Item Id. 980003

The angular sawing drilling heads G25-1.2-SB have a machining spindle continuously adjustable by scale. The adjustment range is 0° (vertical) up to 100° to both sides. The spindle turning direction is opposite to drive turning direction. The drive speed is transmitted in a ratio of 1:1,48 to the tool receptacle. The maximum spindle speed is 12,000 rpm in interval operation.

Variants on demand!

